According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Morlina S3 BA 220

Version 1.2	Revision Date: 06/02/2021	SDS Number: 800010025903	
SECTION	1. IDENTIFICATION		
Produ	uct name	: Shell Morlina S	S3 BA 220
Produ	uct code	: 001F8465	
Manu	afacturer or supplier's	s details	
Manu	ifacturer/Supplier	: Shell Oil Proc PO Box 4427 Houston TX 7 USA	
	Request omer Service	: (+1) 877-276- <sup>-</sup> :	7285
Spill I		n <b>ber</b> : 877-504-9351 : 877-242-7400	
	mmended use of the mmended use	<b>chemical and restri</b> : Machine oil.	ctions on use

### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements		
Hazard pictograms	: N	No Hazard Symbol required
Signal word	:	No signal word
Hazard statements	-	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements		Prevention: No precautionary phrases. Response: No precautionary phrases. Storage: No precautionary phrases.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### Shell Morlina S3 BA 220

Version	Revision Date:
1.2	06/02/2021

SDS Number: 800010025903

Print Date: 06/03/2021 Date of last issue: 05/16/2017

### Disposal:

No precautionary phrases.

### Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
Chemical nature	:	Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. Classification based on DMSO extract content < 3% (Regula- tion (EC) 1272/2008, Annex VI, Part 3, Note L).

### Hazardous components

SECTION 4. FIRST-AID MEASURES					
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.			
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.			
If swallowed	:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.			
Most important symptoms and effects, both acute and delayed	:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.			
Protection of first-aiders	:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.			
Indication of any immediate medical attention and special treatment needed	:	Treat symptomatically.			

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Morlina S3 BA 220

Version	Revision Date:	SDS Number:	Print Date: 06/03/2021
1.2	06/02/2021	800010025903	Date of last issue: 05/16/2017

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice	:	For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

### SECTION 7. HANDLING AND STORAGE

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### Shell Morlina S3 BA 220

Vers 1.2	ion Revision Date: 06/02/2021		OS Number: 0010025903	Print Date: 06/03/2021 Date of last issue: 05/16/2017	
Technical measures		:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.		
Advice on safe handling		:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate rials in order to prevent fires.		
	Avoidance of contact	:	Strong oxidising a	gents.	
Product Transfer		:	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation		
	Further information on stor- age stability	:	place.	htly closed and in a cool, well-ventilated led and closable containers.	
			Store at ambient t	emperature.	
	Packaging material	:	Suitable material: steel or high dens Unsuitable materi		
	Container Advice	:		ainers should not be exposed to high tem- e of possible risk of distortion.	

### SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Components with workplace control parameters

	-			
Components	CAS-No.	Value type (Form of	Control parame- ters / Permissible	Basis
		exposure)	concentration	
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral		TWA (Inhal-	5 mg/m3	ACGIH
		able particu-		
		late matter)		

### **Biological occupational exposure limits**

No biological limit allocated.

### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### Shell Morlina S3 BA 220

Version	Revision Date:	SDS Number:	Print Date: 06/03/2021
1.2	06/02/2021	800010025903	Date of last issue: 05/16/2017

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available. National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/ Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/ Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/ Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil **Engineering measures** The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping. Personal protective equipment Respiratory protection No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.

Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appro-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Morlina S3 BA 220

2	Revision Date: 06/02/2021	SDS Number: 800010025903	Print Date: 06/03/2021 Date of last issue: 05/16/2017
		Select a filter	ation of mask and filter. suitable for the combination of organic gases and particles [Type A/Type P boiling point ;)].
Hand pr Rem		gloves approv US: F739) ma suitable chem gloves Suitab usage, e.g. fr sistance of glo glove supplie Personal hyg Gloves must gloves, hands cation of a no For continuou through time 480 minutes v short-term/sp recognize tha may not be av time maybe a and replacem a good predic dependent or Glove thickne	contact with the product may occur the use of ved to relevant standards (e.g. Europe: EN374, ade from the following materials may provide nical protection. PVC, neoprene or nitrile rubber ility and durability of a glove is dependent on equency and duration of contact, chemical re- ove material, dexterity. Always seek advice from rs. Contaminated gloves should be replaced. iene is a key element of effective hand care. only be worn on clean hands. After using a should be washed and dried thoroughly. Appli- in-perfumed moisturizer is recommended. Is contact we recommend gloves with break- of more than 240 minutes with preference for > where suitable gloves can be identified. For lash protection we recommend the same but t suitable gloves offering this level of protection vailable and in this case a lower breakthrough cceptable so long as appropriate maintenance tent regimes are followed. Glove thickness is not ent regimes are followed. Glove thickness is not and the same but the same but the same but the same but the exact composition of the glove material.
Eye prot	tection		nandled such that it could be splashed into eyes, ewear is recommended.
Skin and	d body protection	work clothes.	on is not ordinarily required beyond standard ctice to wear chemical resistant gloves.
Protectiv	ve measures		ective equipment (PPE) should meet recom- nal standards. Check with PPE suppliers.
Therma	l hazards	: Not applicable	e

General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Morlina S3 BA 220

Ve	ersion	Revision Date:	SDS Number:	Print Date: 06/03/2021
1.:	2	06/02/2021	800010025903	Date of last issue: 05/16/2017

		vapour.
CTION 9. PHYSICAL AND CHE	MIC	CAL PROPERTIES
Appearance	:	liquid
Colour	:	amber
Odour	:	Data not available
Odour Threshold	:	Data not available
рН	:	Not applicable
pour point	:	Method: Unspecified
Melting point/freezing point		Data not available
Initial boiling point and boiling range	:	> 280 °C / 536 °F estimated value(s)
Flash point	:	>= 220 °C / >= 428 °F
		Method: ASTM D92 (COC)
Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Data not available
Upper explosion limit / upper flammability limit	:	Typical 10 %(V)
Lower explosion limit / Lower flammability limit	:	Typical 1 %(V)
Vapour pressure	:	< 0.5 Pa (20 °C / 68 °F)
		estimated value(s)
Relative vapour density	:	> 1 estimated value(s)
Relative density	:	0.880 (15 °C / 59 °F)
Density	:	880 kg/m3 (15.0 °C / 59.0 °F) Method: DIN EN ISO 12185
Solubility(ies) Water solubility	:	negligible
Solubility in other solvents	:	Data not available
Partition coefficient: n- octanol/water	:	log Pow: > 6 (based on information on similar products)

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### Shell Morlina S3 BA 220

Version 1.2	Revision Date: 06/02/2021		S Number: 0010025903	Print Date: 06/03/2021 Date of last issue: 05/16/2017		
Auto	Auto-ignition temperature Decomposition temperature		> 320 °C / 608 °l	-		
Dec			: Data not available			
	osity /iscosity, dynamic	:	Data not availab	le		
١	Viscosity, kinematic		198 - 242 mm2/s	s (40 °C / 104 °F)		
			Method: ASTM	0445		
Exp	losive properties	:	Not classified			
Oxio	lizing properties	:	Data not availab	le		
Con	ductivity	:	This material is r	not expected to be a static accumulator.		

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
Possibility of hazardous reac- tions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

### SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

#### Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

### Acute toxicity

#### Product:

Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### Shell Morlina S3 BA 220

Version 1.2	Revision Date: 06/02/2021	SDS Number: 800010025903	Print Date: 06/03/2021 Date of last issue: 05/16/2017
		are not met.	
Acute dermal toxicity		: LD50 (Rabbit): Remarks: Low Based on availa	

### Skin corrosion/irritation

### Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

### Serious eye damage/eye irritation

### Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

### Respiratory or skin sensitisation

### Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

### Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

### Carcinogenicity

### Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### Shell Morlina S3 BA 220

Version	Revision Date:	SDS Number:	Print Date: 06/03/2021
1.2	06/02/2021	800010025903	Date of last issue: 05/16/2017

by NTP.

÷

### **Reproductive toxicity**

### Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

### STOT - single exposure

### Product:

Remarks: Based on available data, the classification criteria are not met.

### STOT - repeated exposure

### Product:

Remarks: Based on available data, the classification criteria are not met.

### Aspiration toxicity

### Product:

Not an aspiration hazard.

### **Further information**

### Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

### SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment	: Ecotoxicological data have not been determined specifically for this product.
	Information given is based on a knowledge of the components and the ecotoxicology of similar products.
	Unless indicated otherwise, the data presented is representa-
	tive of the product as a whole, rather than for individual com-
	ponent(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Morlina S3 BA 220

Vers 1.2	sion	Revision Date: 06/02/2021		9S Number: 0010025903	Print Date: 06/03/2021 Date of last issue: 05/16/2017
	Ecotox	licity			
	Product Toxicity ty)	<mark>≿t:</mark> ⁄ to fish (Acute toxici-	:	Remarks: Based of are not met. Practically non to LL/EL/IL50 > 100	
		<i>t</i> to daphnia and other invertebrates (Acute )	:	Remarks: Based of are not met. Practically non toy LL/EL/IL50 > 100	
	Toxicity icity)	/ to algae (Acute tox-	:	Remarks: Based of are not met. Practically non tox LL/EL/IL50 > 100	
	Toxicity icity)	v to fish (Chronic tox-	:	Remarks: Based of are not met.	on available data, the classification criteria
		/ to daphnia and other invertebrates (Chron- ity)	:	Remarks: Based of are not met.	on available data, the classification criteria
		/ to microorganisms toxicity)	:	Remarks: Based of are not met.	on available data, the classification criteria
	Persist	ence and degradabili	ity		
	Produc	<u>:t:</u>			
		radability	:	Major constituents components that in Persistent per IMO International Oil P tion: "A non-persis consists of hydroc by volume, distills at least 95% of wh	ollution Compensation (IOPC) Fund defini- stent oil is oil, which, at the time of shipment, arbon fractions, (a) at least 50% of which, at a temperature of 340°C (645°F) and (b) hich, by volume, distils at a temperature of en tested by the ASTM Method D-86/78 or
	Bioacc	umulative potential			
	<u>Produc</u> Bioacci	<u>st:</u> umulation	:	Remarks: Contain cumulate.	s components with the potential to bioac-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Morlina S3 BA 220

Version 1.2	Revision Date: 06/02/2021	SDS Number: 800010025903	Print Date: 06/03/2021 Date of last issue: 05/16/2017			
Mobi	lity in soil					
<u>Prod</u> ı Mobil		: Remarks: Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile.				
Othe	r adverse effects	Remarks: Floa	ats on water.			
<u>Prod</u> e Additi matio	onal ecological infor-	ozone creation Product is a m	e ozone depletion potential, photochemical n potential or global warming potential. hixture of non-volatile components, which will not o air in any significant quantities under normal use.			
		Mineral oil doe	mixture. cal fouling of aquatic organisms. es not cause chronic toxicity to aquatic organ- ntrations less than 1 mg/l.			

### SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	<ul> <li>Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be deforehand.</li> </ul>
	MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides tech- nical aspects at controlling pollutions from ships.
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional,

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### Shell Morlina S3 BA 220

Version 1.2	Revision Date: 06/02/2021	SDS Number: 800010025903	Print Date: 06/03/2021 Date of last issue: 05/16/2017
		national, and lo	cal laws and regulations.
Local legislation Remarks			d be in accordance with applicable regional, cal laws and regulations.

### **SECTION 14. TRANSPORT INFORMATION**

### **National Regulations**

### US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

### International Regulations

IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

#### Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

### **SECTION 15. REGULATORY INFORMATION**

### EPCRA - Emergency Planning and Community Right-to-Know Act

### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Naphthalene	91-20-3	100	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### Shell Morlina S3 BA 220

Version 1.2	Revision Date: 06/02/2021	SDS Number: 800010025903	Print Date: 06/03/2021 Date of last issue: 05/16/2017			
SAR/	A 313	known CAS nu	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.			
Clear	Water Act					
The fo 117.3	-	chemicals are listed un	der the U.S. CleanWater Act, Section 311, Table			
117.5	Naphthalene	91-20-3	0.0007 %			
US St	tate Regulations					
Penn	sylvania Right To K	now				
	Distillates (petro	leum), solvent-dewaxe leum), hydrotreated he leum), hydrotreated lig	avy paraffinic 64742-54-7			
WAR			nicals including Naphthalene, which is/are known re information go to www.P65Warnings.ca.gov.			
Other	r regulations:					
	egulatory information material.	is not intended to be c	omprehensive. Other regulations may apply			
The components of this product are reported in the following inventories:						
REAC	•	: Not establishe	-			
TSCA	١	: All components	s listed.			
DSL						

### **SECTION 16. OTHER INFORMATION**

### Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average
Abbreviations and Acronyms		The standard abbreviations and acronyms used in this docu- ment can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.
		ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Morlina S3 BA 220

Version Revisi	on Date: SDS Number:	Print Date: 06/03/2021
1.2 06/02/	2021 800010025903	Date of last issue: 05/16/2017
	AICS = Austra ASTM = Amer BEL = Biologia BTEX = Benz CAS = Chemia CEFIC = Euro CLP = Classifi COC = Clevel DIN = Deutsch DMEL = Deriv DNEL = Deriv DNEL = Deriv DNEL = Deriv DSL = Canada EC = Europea EC50 = Effect ECETOC = Eu gy Of Chemica ECHA = Europ EINECS = The Chemical Sub EL50 = Effecti ENCS = Japai Inventory EWC = Europ GHS = Global Labelling of C IARC = Interna IC50 = Inhibito IL50 = Inhibito IL50 = Inhibito IMDG = Interna INV = Chinese IP346 = Instit determination KECI = Korea LC50 = Lethal LD50 = Lethal LD50 = Lethal LD50 = Lethal MARPOL = In Pollution From NOEC/NOEL served Effect OE_HPV = OC PBT = Persist PICCS = Phili Substances PNEC = Predi REACH = Reg Chemicals RID = Regulat gerous Goods SKIN_DES = 5	pean Chemicals Agency e European Inventory of Existing Commercial stances ive Loading fifty nese Existing and New Chemical Substances ean Waste Code lly Harmonised System of Classification and hemicals ational Agency for Research on Cancer ational Air Transport Association ory Concentration fifty ory Level fifty hational Maritime Dangerous Goods e Chemicals Inventory ute of Petroleum test method N° 346 for the of polycyclic aromatics DMSO-extractables Existing Chemicals Inventory I Concentration fifty I Dose fifty per cent. thal Loading/Effective Loading/Inhibitory loading Loading fifty ternational Convention for the Prevention of n Ships = No Observed Effect Concentration / No Ob- Level ccupational Exposure - High Production Volume ent, Bioaccumulative and Toxic ppine Inventory of Chemicals and Chemical icted No Effect Concentration Of tions Relating to International Carriage of Dan-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### Shell Morlina S3 BA 220

Version	Revision Date:	SDS Number:	Print Date: 06/03/2021
1.2	06/02/2021	800010025903	Date of last issue: 05/16/2017

TSCA = US Toxic Substances Control Act TWA = Time-Weighted Average vPvB = very Persistent and very Bioaccumulative

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Revision Date : 06/02/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN